

Manual Nanolex Premium Convertible Top Sealant

Product description:

Nanolex Premium Convertible Top Sealant is a hydrophobic surface impregnation based on chemical nanotechnology. It forms a transparent and ultra thin layer on absorbing surfaces and shows oil and water repelling properties.

This product can be stored for up to 24 months (in a dry, temperature stable environment)

Consumption:

Sealant: appr. 40-50ml/m² (~150 ml for one soft top)

Processing temperature: 5-30°C - Avoid direct sunlight and/or high air humidity.

SAFETY REFERENCE:

The usual behavior rules regarding chemical substances are to be followed during the use of all car care products: Make sure that the room you work in is ventilated enough. In case you have eye contact rinse the eyes out for at least 15 minutes, especially under the eyelids. In case a liquid was swallowed make sure you drink a lot of water and avoid to vomit – see a doctor immediatly. Keep out of the reach of children. Keep out of surface water and drains.

The following steps are recommended to obtain the best results:

Cleaning

The surface must be free of dust and pollution to ensure the best impregnation performance and durability.

Shake well before use

Application of Nanolex Premium Convertible Top Sealant

Nanolex Premium Convertible Top Sealant is to be applied by spraying or dipping. Long time experience shows that the best solution is to spray the sealant on a sponge and then spread it evenly on the fabric. The surface must be completely saturated. Consumption depends on substrate suction. The sealant dries and cures at room temperature. Avoid drying at higher temperatures because of possible forming of explosive mixings with air.

Cleaning: With water or damp cloth.

Disposal: Dispose bundles with remains according to your local laws

nanolex

Read carefully:

The information on this data sheet is based on the current status of technical development as well as our experience with the product. However, given the variety of surfaces and ambient conditions, the information provided on this data sheet shall in no way diminish the responsibility of the user to ensure with due care, that our product is suited for the intended purpose, surface and application conditions. Since application and processing lie outside our purview, no manufacturer liability shall be derived from the information provided herein. Our General Terms and Conditions of business shall apply in all cases. All information is subject to change without notice.

Contact:

Nano Surface Solutions
Am Liedersberg 17a
66399 Mandelbachtal
Germany

Phone: 00496803984057
Fax: 004968038647
E-mail: info@nanosurfacesolutions.com
TaxNr.: 085/238/04899

UST-ID DE258993010

Director: Florian Kessler



nanolex