

Manual Nanolex Premium Glass Sealant

Product description:

Improved water repelling characteristics mean more security and better view. The non-adhesive - surface can be cleaned at drastically reduced work expenditure and released easily from ice.

This product can be stored for up to 24 months (in a dry, temperature stable environment)

Consumption:

Cleaner: appr. 10ml/m² (~50 ml for all car glass surfaces)

Sealant: appr. 5ml/m² (~15 ml for all car glass surfaces or ~3-5ml for one windshield)

Processing temperature: 5-30°C - Avoid direct sunlight and/or high air humidity.

SAFETY REFERENCE:

The usual behavior rules regarding chemical substances are to be followed during the use of all car care products: Make sure that the room you work in is ventilated enough. In case you have eye contact rinse the eyes out for at least 15 minutes, especially under the eyelids. In case a liquid was swallowed make sure you drink a lot of water and avoid to vomit – see a doctor immediatly. Keep out of the reach of children. Keep out of surface water and drains.

The following steps are recommended to obtain the best results:

Clean the inside of the car windows with normal glass cleaner to avoid irritations when removing the grey veil after the application of Nanolex Premium Glass Sealant. Also clean wiper blades and seals around the windshield.

Cleaning

Nanolex Premium Glass Cleaner

Shake well before use

Put ~5 ml of the cleaner on a lint free cloth and clean the glass thoroughly until the complete glass surface is absolutely clean. This step is absolutely crucial in order to achieve a durable result. Use water or alcohol as a last step to make sure that all glass cleaner residue is removed.

Also make sure to clean the windshield wipers as well before they are used on the sealed surface. Dirty windshield wipers can easily damage the fresh sealant!

Application of Nanolex Premium Glass Sealant

Shake the bottle that contains the sealant very well before use

Take a soft cotton cloth/makeup pad and pour a few drops of the sealant on it (start with small amounts, there is only very little amounts necessary).

Moisten all the car windows evenly with firm pressure on the pad. With correct application you can now see a light grey veil on the windows.

Polish away the grey veils after all solvents have steamed off, use a clean (microfiber) cloth.

After the windows are polished do not touch them and protect them from

humidity. The sealant needs about 2 hours to fully cure.

After the drying polish the windshield and windows again with a lint free cloth to remove the last grey veil-leftovers and to optimize the refinement.

Tips:

Wiping water additives impairs the dripping off characteristics temporarily or lead to the creation of cloudy stains:

- empty the wiping water tank and fill it with only plain water
- In the winter add additives (freeze protection) only in low proportion

Because of the missing water film wipers are inclined to create cloudy stains.

If this does not disappear after the break-in period:

- Clean the wiper blades with pure alcohol
- Replace used and hard wiper blades
- Change the angles of incidence and contact pressure of the windshield wipers

Cleaning: With water or damp cloth. Wipe the glass surfaces with white spirits for revitalization.

Disposal: Dispose bundles with remains according to your local laws

Read carefully:

The information on this data sheet is based on the current status of technical development as well as our experience with the product.

However, given the variety of surfaces and ambient conditions, the information provided on this data sheet shall in no way diminish the responsibility of the user to ensure with due care, that our product is suited for the intended purpose, surface and application conditions.

Since application and processing lie outside our purview, no manufacturer liability shall be derived from the information provided herein. Our General Terms and Conditions of business shall apply in all cases. All information is subject to change without notice.

Read carefully

The information on this data sheet is based on the current status of technical development as well as our experience with the product. However, given the variety of surfaces and ambient conditions, the information provided on this data sheet shall in no way diminish the responsibility of the user to ensure with due care, that our product is suited for the intended purpose, surface and application conditions.

Since application and processing lie outside our purview, no manufacturer liability shall be derived from the information provided herein. Our General Terms and Conditions of business shall apply in all cases. All information is subject to change without notice.

Contact:

Nano Surface Solutions
Am Liedersberg 17a
66399 Mandelbachtal
Germany

Phone: 00496803984057

Fax: 004968038647

E-mail: info@nanosurfacesolutions.com

TaxNr.: 085/238/04899

UST-ID DE258993010

Director: Florian Kessler